

VALVOLE APR UNLOADER VALVES - REGULATEURS - REGULADORES

customized
PRECISION

highest
QUALITY

state
OF THE ART

Valvole regolazione pressione, attacco con viti cave pompe serie: WB-WBX

Unloader valves with banjo connections for pumps WB-WBX series

Régulateurs de pression avec vis de fixation pour pompes série WB-WBX

Válvulas de regulación de presión, conexión con tornillos de fijación para bombas WB-WBX

Temperatura max: 60°C - 140°F

Max temperature: 60°C - 140°F

Température max: 60°C - 140°F

Temperatura máx: 60°C - 140°F

APR 20



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW l/min GPM | Attacco pompa Port size BSP | Entrata Inlet BSP | Uscita Outlet | PESO WEIGHT | |
|---------------------|--------|---------------|----------------------------|------|---------------------------|--------------------------------|----------------------|---------------|-------------|-----|
| | | | BAR | PSI | | | | | Kg | lbs |
| 05.8708.97.3 | Orange | APR 20 | 140 | 2000 | 21 5.5 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 0.86 | 1.9 |
| 05.8711.97.3 | Orange | APR 20 | 140 | 2000 | 21 5.5 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 0.90 | 2.0 |

APR.I 20



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW l/min GPM | Attacco pompa Port size BSP | Entrata Inlet BSP | Uscita Outlet | PESO WEIGHT | |
|---------------------|--------|--|----------------------------|------|---------------------------|--------------------------------|----------------------|---------------|-------------|-----|
| | | | BAR | PSI | | | | | Kg | lbs |
| 05.8707.97.3 | Orange | APR.I 20 Fixed injector 1.6 (*) | 140 | 2000 | 15 4 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 0.90 | 2.0 |
| 05.8710.97.3 | Orange | APR.I 20 Fixed injector 1.6 (*) | 140 | 2000 | 15 4 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 0.95 | 2.1 |
| 05.8706.97.3 | Orange | APR.I 20 Adjust injector 1.6 (*) | 140 | 2000 | 15 4 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 0.90 | 2.0 |
| 05.8709.97.3 | Orange | APR.I 20 Adjust injector 1.6 (*) | 140 | 2000 | 15 4 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 0.95 | 2.1 |

APR 25



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW l/min GPM | Attacco pompa Port size BSP | Entrata Inlet BSP | Uscita Outlet | PESO WEIGHT | |
|---------------------|-------|---------------|----------------------------|------|---------------------------|--------------------------------|----------------------|---------------|-------------|-----|
| | | | BAR | PSI | | | | | Kg | lbs |
| 05.8714.97.3 | Blue | APR 25 | 175 | 2500 | 21 5.5 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 0.86 | 1.9 |
| 05.8717.97.3 | Blue | APR 25 | 175 | 2500 | 21 5.5 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 0.90 | 2.0 |

APR.I 25



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW l/min GPM | Attacco pompa Port size BSP | Entrata Inlet BSP | Uscita Outlet | PESO WEIGHT | |
|---------------------|-------|--|----------------------------|------|---------------------------|--------------------------------|----------------------|---------------|-------------|-----|
| | | | BAR | PSI | | | | | Kg | lbs |
| 05.8713.97.3 | Blue | APR.I 25 Fixed injector 1.6 (*) | 175 | 2500 | 15 4 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 0.90 | 2.0 |
| 05.8716.97.3 | Blue | APR.I 25 Fixed injector 1.6 (*) | 175 | 2500 | 15 4 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 0.95 | 2.1 |
| 05.8712.97.3 | Blue | APR.I 25 Adjust injector 1.6 (*) | 175 | 2500 | 15 4 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 0.90 | 2.0 |
| 05.8715.97.3 | Blue | APR.I 25 Adjust injector 1.6 (*) | 175 | 2500 | 15 4 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 0.95 | 2.1 |

(*) Optional ugello eiettore 1.8 - 2.1 - 2.3 -Optional injector nozzle 1.8 - 2.1 - 2.3

Optionnel buse injecteur 1.8 - 2.1 - 2.3 -Opción boquilla eyectora 1.8 - 2.1 - 2.3

(**) Versione speciale per umidificazione: stesso codice con ultima cifra "B" in sostituzione del "3"

Special version for misting/fogging: the same part nr. with the last figure "B" that replaces "3"

Version spéciale pour brumisation: la même référence avec la dernière lettre "B" qui remplace "3"

Versión especial para humidificación: el mismo código con la última cifra "B" que reemplaza el "3"

Valvole regolazione pressione, attacco con viti cave pompe serie: WM-TM

Unloader valves with banjo connections for pumps WM-TM series

Régulateurs de pression avec vis de fixation pour pompes série WM-TM

Válvulas de regulación de presión, conexión con tornillos de fijación para bombas WM-TM

Temperatura max: 60°C - 140°F

Max temperature: 60°C - 140°F

Température max: 60°C - 140°F

Temperatura máx: 60°C - 140°F

APR 30



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW | | Attacco pompa Port size | Entrata Inlet | Uscita Outlet | PESO WEIGHT | |
|---------------------|-------|---------------|----------------------------|------|--------------|-----|-------------------------|---------------|---------------|-------------|-----|
| | | | BAR | PSI | l/min | GPM | BSP | BSP | | Kg | lbs |
| 05.8720.97.3 | Blue | APR 30 | 210 | 3000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 3/8 BSP - M | 0.86 | 1.9 |
| 05.8723.97.3 | Blue | APR 30 | 210 | 3000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 22x1.5 - M | 0.90 | 2.0 |

APR.I 30



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW | | Attacco pompa Port size | Entrata Inlet | Uscita Outlet | PESO WEIGHT | |
|---------------------|-------|--|----------------------------|------|--------------|-----|-------------------------|---------------|---------------|-------------|-----|
| | | | BAR | PSI | l/min | GPM | BSP | BSP | | Kg | lbs |
| 05.8719.97.3 | Blue | APR.I 30 Fixed injector 1.6 (*) | 210 | 3000 | 15 | 4 | 3/8 1/2 | 1/2 - M | 3/8 BSP - M | 0.90 | 2.0 |
| 05.8722.97.3 | Blue | APR.I 30 Fixed injector 1.6 (*) | 210 | 3000 | 15 | 4 | 3/8 1/2 | 1/2 - M | 22x1.5 - M | 0.95 | 2.1 |
| 05.8718.97.3 | Blue | APR.I 30 Adjust injector 1.6 (*) | 210 | 3000 | 15 | 4 | 3/8 1/2 | 1/2 - M | 3/8 BSP - M | 0.90 | 2.0 |
| 05.8721.97.3 | Blue | APR.I 30 Adjust injector 1.6 (*) | 210 | 3000 | 15 | 4 | 3/8 1/2 | 1/2 - M | 22x1.5 - M | 0.95 | 2.1 |

Valvole regolazione pressione, attacco con viti cave pompe serie: WBX

Unloader valves with banjo connections for pumps WBX series

Régulateurs de pression avec vis de fixation pour pompes série WBX

Válvulas de regulación de presión, conexión con tornillos de fijación para bombas WBX

Temperatura max: 60°C - 140°F

Max temperature: 60°C - 140°F

Température max: 60°C - 140°F

Temperatura máx: 60°C - 140°F

APR 35



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW | | Attacco pompa Port size | Entrata Inlet | Uscita Outlet | PESO WEIGHT | |
|---------------------|-------|---------------|----------------------------|------|--------------|-----|-------------------------|---------------|---------------|-------------|-----|
| | | | BAR | PSI | l/min | GPM | BSP | BSP | | Kg | lbs |
| 05.8751.97.3 | Green | APR 35 | 240 | 3500 | 21 | 5.5 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 1.10 | 2.4 |
| 05.8754.97.3 | Green | APR 35 | 240 | 3500 | 21 | 5.5 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 1.15 | 2.5 |

APR.I 35



| CODICE CODE (**) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW | | Attacco pompa Port size | Entrata Inlet | Uscita Outlet | PESO WEIGHT | |
|---------------------|-------|--|----------------------------|------|--------------|-----|-------------------------|---------------|---------------|-------------|------|
| | | | BAR | PSI | l/min | GPM | BSP | BSP | | Kg | lbs |
| 05.8752.97.3 | Green | APR.I 35 Fixed injector 1.6 (*) | 240 | 3500 | 15 | 4 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 1.15 | 2.5 |
| 05.8755.97.3 | Green | APR.I 35 Fixed injector 1.6 (*) | 240 | 3500 | 15 | 4 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 1.20 | 2.65 |
| 05.8753.97.3 | Green | APR.I 35 Adjust injector 1.6 (*) | 240 | 3500 | 15 | 4 | 3/8 3/8 | 1/2 - M | 3/8 BSP - M | 1.15 | 2.5 |
| 05.8759.97.3 | Green | APR.I 35 Adjust injector 1.6 (*) | 240 | 3500 | 15 | 4 | 3/8 3/8 | 1/2 - M | 22x1.5 - M | 1.20 | 2.65 |

(*) Optional ugello eiettore 1.8 - 2.1 - 2.3 -Optional injector nozzle 1.8 - 2.1 - 2.3

Optionnel buse injecteur 1.8 - 2.1 - 2.3 -Opción boquilla eyectora 1.8 - 2.1 - 2.3

(**) Versione speciale per umidificazione: stesso codice con ultima cifra "B" in sostituzione del "3"

Special version for misting/fogging: the same part nr. with the last figure "B" that replaces "3"

Version spéciale pour brumisation: la même référence avec la dernière lettre "B" qui remplace "3"

Versión especial para humidificación: el mismo código con la última cifra "B" que reemplaza el "3"

VALVOLE APR UNLOADER VALVES - REGULATEURS - REGULADORES

customized
PRECISION

highest
QUALITY

state
OF THE ART

Valvole regolazione pressione, attacco con viti cave pompe serie: WM - TM

Unloader valves with banjo connections for pumps WM - TM series

Régulateurs de pression avec vis de fixation pour pompes série WM - TM

Válvulas de regulación de presión, conexión con tornillos de fijación para bombas WM - TM

Temperatura max: 60°C - 140°F

Max temperature: 60°C - 140°F

Température max: 60°C - 140°F

Temperatura máx: 60°C - 140°F

APR 40



| CODICE CODE (*) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW | | Attacco pompa Port size | Entrata Inlet | Uscita Outlet | PESO WEIGHT | |
|-----------------|-------|---------------|----------------------------|------|--------------|-----|-------------------------|---------------|---------------|-------------|-----|
| | | | BAR | PSI | l/min | GPM | BSP | BSP | | Kg | lbs |
| 05.8702.97.3 | Green | APR 40 | 280 | 4000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 3/8 BSP - M | 1.10 | 2.4 |
| 05.8705.97.3 | Green | APR 40 | 280 | 4000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 22x1.5 - M | 1.15 | 2.5 |

APR.I 40



| CODICE CODE (*) | COLOR | MODELLO MODEL | PRESSIONE MAX MAX PRESSURE | | PORTATA FLOW | | Attacco pompa Port size | Entrata Inlet | Uscita Outlet | PESO WEIGHT | |
|-----------------|-------|--|----------------------------|------|--------------|-----|-------------------------|---------------|---------------|-------------|------|
| | | | BAR | PSI | l/min | GPM | BSP | BSP | | Kg | lbs |
| 05.8701.97.3 | Green | APR.I 40 Fixed injector 2.1 (*) | 280 | 4000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 3/8 BSP - M | 1.15 | 2.5 |
| 05.8704.97.3 | Green | APR.I 40 Fixed injector 2.1 (*) | 280 | 4000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 22x1.5 - M | 1.20 | 2.65 |
| 05.8700.97.3 | Green | APR.I 40 Adjust injector 2.1 (*) | 280 | 4000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 3/8 BSP - M | 1.15 | 2.5 |
| 05.8703.97.3 | Green | APR.I 40 Adjust injector 2.1 (*) | 280 | 4000 | 21 | 5.5 | 3/8 1/2 | 1/2 - M | 22x1.5 - M | 1.20 | 2.65 |

(*) Optional ugello eiettore 1.6 - 1.8 - 2.3 -Optional injector nozzle 1.6 - 1.8 - 2.3

Optionel buse injecteur 1.6 - 1.8 - 2.3 -Opción boquilla eyectora 1.6 - 1.8 - 2.3

(**) Versione speciale per umidificazione: stesso codice con ultima cifra "B" in sostituzione del "3"

Special version for misting/fogging: the same part nr. with the last figure "B" that replaces "3"

Version spéciale pour brumisation : la même référence avec la dernière lettre "B" qui remplace "3"

Versión especial para humidificación : el mismo código con la última cifra "B" que reemplaza el "3"

SCHEMA INSTALLAZIONE VALVOLA APR.I UNLOADER VALVES APR.I-INSTALLATION

